

| OASIS™



MOLTEN METAL SPLASH PROTECTION

Oasis™ 1000

MAXIMUM PROTECTION AGAINST MOLTEN METALS

Rated to D3 / E3 protection, Oasis™ 1000 offers the highest level of protection against aluminum and iron splash.

SUPER-WASH WOOL FOR ENHANCED DURABILITY

Super-wash wool allows for greater garment durability through heavy wash and wear thanks to superior abrasion resistance.

LEGACY OF QUALITY

Trusted for decades by leading professionals around the globe, the Oasis™ brand is synonymous with quality.

OASIS™

TECHNICAL DATA*	OASIS™ 1000
Nominal Weight	10.0 osy (340 gsm)
Construction	Woven
Color	Dark Gray, Dark Navy, Navy Blue, Orange
Fiber Content	FR Rayon, Wool, Nylon
Certification(s)	ISO 11612

Flame Resistance			
Arc Thermal Performance Value NFPA 70E, ASTM 1959	ATPV Rating		7.5 cal/cm ²
	PPE Category		Category 1
Vertical Flame ASTM 6413	Initial and 100x after wash	After flame	< 2.0 sec
		Char length	< 5.0 in (127 mm)
Molten Metal Splash ISO 9185	Molten Aluminum Rating		D3
	Molten Iron Rating		E3

Comfort		
Crocking AATCC 8	Wet	Up to 4.0 - 5.0 *
	Dry	Up to 5.0 *

* All values subject to final certification and specification. Tested on specific colors. Appearance is dependent on shade of fabric.

AVAILABLE COLORS				OPTIONAL COLORS
Dark Gray	Dark Navy	Navy	Orange	Additional color options may be available. Please contact TenCate Protective Fabrics for more information.
				Color shades and textures may vary. Please contact your sales representative for swatch samples.



STANDARD 100
1807065
Centexbel

TenCate Protective Fabrics
is certified according:



Corporate
Social
Responsibility

All mentioned data must be considered as indicative values. To the best of our knowledge all information contained herein is accurate. TenCate Protective Fabrics declines any form of liability related to the use of the attached specimen that shall be regarded as a sample only and therefore not meant to be used in any form of garment making.